


OTHER TYPE
 1. ROTARY
 2. FLAP
 3. ANGLE
 RANGE-UP TO1500 #

Di.a. D	25	25	42	50	60	80	100	130
A	105	105	125	155	178	190	215	250
Size mm	15	20	25	40	50	65	80	100

No.	NAME	MATERIAL	Qty.	Nos.	REMARKS		
6	Customers	CAF	CAF	PTFE	PTFE	2	
5	Saskets	CAF	CAF	PTFE	PTFE	2	
4	Bot Nuts	MS	HT	AISI-304	AISI-304	8	
3	Cover	SGI	WCB	CF8	CF8M	2	
2	Windows	Tempered Soda/lime/Borosilicate/As required				2	
1	Body	CI	WCB	CF8	CF8M	1	

Hydrostatic Test Pressure	15 Kgs./Sq. Cms	Design Reference	ASME/ANSI-B16.5-1988 Ed
Flanges to	ANSI-B-16.5 Class-150 R.F. Serrated	Testing Reference	API-598-7Th-ED-1996
		NDT -On Request	All but weld joints 100 % Radiographic tested

NAME	DATE	CLIENT:
DRN AMP	16/10	 PROCESS EQUIPMENT CORPORATION AHMEDABAD-380008,INDIA
DGN PMM	16/10	
CHD PMM	16/10	
APPR		
DRG		
SCALE: NTS		TITLE: ANCHOR SIGHT FLOW INDICATOR-DRIP TYPE
MATTL: AS REQUIRED		
Model-Code-SFI-03-A10FAC000		
Drg No: 03-SFI-A10FAC000		Location
REV.No-A0 REV.Dt.27/07/2020		SFI-03-A10FAC000-DRG-ASS