



OTHER TYPE
1. ROTARY
2. FLAP
3. ANGLE
RANGE-UP TO 1500 #

| Dia. D | 25 | 25 | 42 | 50 | 60 | 80 | 100 | 130 |
|------------|-----|-----|-----|-----|-----|-----|-----|-----|
| A | 105 | 105 | 125 | 165 | 178 | 190 | 215 | 250 |
| Size mm/IN | 15 | 20 | 25 | 40 | 50 | 65 | 80 | 100 |

| No. | NAME | MATERIAL | Qty. | Nos. | REMARKS |
|-----|------------|--|----------|----------|---------|
| 7 | Rotor | AISI-316 | AISI-316 | AISI-316 | 1 |
| 6 | Cushioners | CAF | PTFE | PTFE | 2 |
| 5 | Gaskets | CAF | PTFE | PTFE | 2 |
| 4 | Bolt Nuts | HT | AISI-304 | AISI-304 | 8 |
| 3 | Cover | WCB | CF8 | CF8M | 2 |
| 2 | Windows | Tempered Sodalime/Borosilicate/As required | | | 2 |
| 1 | Body | WCB | CF8 | CF8M | 1 |

| | | | |
|---------------------------|-------------------------------------|-------------------|---|
| Hydrostatic Test Pressure | 15 Kgs./Sq. Cms | Design Reference | ASME/ANSI-B16.5-1988 Ed |
| Flanges to | ANSI-B-16.5 Class-150 R.F. Serrated | Testing Reference | API-598-7Th-ED-1996 |
| | | NDT-On Request | All but weld joints 100 % Radiographic tested |

| NAME | DATE | CLIENT: | |
|---|-------------|--|--|
| DRN | AMP | 16/10 | |
| DGN | PMM | 16/10 | |
| CHD | PMM | 16/10 | |
| APPR | | | |
| DRG | | | |
| SCALE: | NTS | PROCESS EQUIPMENT CORPORATION AHMEDABAD-380008,INDIA TITLE: ANCHOR SIGHT FLOW INDICATOR-ROTARY TYPE | |
| MATL: | AS REQUIRED | | |
| AS REQUIRED | | | |
| Drg No: 03-SFI-A30FAC000 REV.No-A0 REV.Dt:27/07/2020 Location SFI-03-A30FAC000-DRG-ASS | | | |